

Fully Engineered

DUAL DECK

VIBRATING SCREENER Pat. Pending

smico

MADE IN USA

Owning a SMICO Dual Deck Screener will provide Excellent Direct Flow Product Classification and High Production with Low Operation Cost

- Rugged-Designed with center inlet for direct flow scalping and inclined deck to rapidly remove overs.
- Versatile-Low profile for fitting between existing silo and bulk truck loading station without having to offset load scales or relocate loading positions.
- Dependable-Low maintenance grease lubricated two bearing centroid mounted drive designed for field service.
- Highly Efficient-Conveying motion is parallel to the sides for minimum degradation, designed to operate at 986 RPM, producing up to 5G's acceleration.
- Flexibility-Simple adjustments allow you to tune amplitude and frequency to your application.
- Smooth-Vibration isolation with coil springs and pivoting motor base.



SMICO Manufacturing Co, L.L.C.

500 North MacArthur Blvd.
Oklahoma City, Oklahoma 73127-5602
Phone: (405)946-1461 (800)351-9088
Fax: (405)946-1472

www.smico.com

SPECIFICATIONS:

TYPICAL APPLICATIONS:

- ◆ Cement
- ◆ Aggregate
- ◆ Sand
- ◆ Feed Pellets
- ◆ Asphalt Ingredients
- ◆ Carbon Black

OPTIONS:

- ◆ Enclosuers
- ◆ Legs
- ◆ Cable Suspension
- ◆ Wear Liners
- ◆ Rubber Isolators
- ◆ Poly Decks
- ◆ High Temp Features
- ◆ Hoppers
- ◆ Spouts
- ◆ Chutes
- ◆ Piano Wire
- ◆ Woven Wire



SIZES:

- ◆ 36" to 72" wide by 6' to 16' long
- ◆ 60 to 110mm FAG Spherical Bearings

